



NBS-2553

3-section anodised aluminium telescopic mast

55mm O.D. base

1.955 metres - Packed

5.35 metres - Extended



NBS-2553
Section Nom. Length: 2 mtr
Bottom Section: Ø55
Sections: 3

Specifications

Construction	Clear anodised aluminium telescopic sections with section stop guides and 2 x passivated D-locking clip
Number of Sections	3
Retracted Height	1.955 metres / 6.41 ft
Extended Height	5.35 metres / 17.55 ft
Weight - excl. D-clips	5.0 kg / 11.02 lbs
Wind Load rating - Max.	160 kph / 99mph - with each section guy wire supported
Top section load rating	10.0 kg / 22.05 lbs
Max. surface area	0.2m ²
Base Section Dimension	O.D: 55mm / 2.16"
2nd Section Dimensions	O.D: 50mm / 1.96"
3rd Section Dimensions	O.D: 45mm / 1.77"
Supplied Accessories	2 x gold passivated section D-clips

Required Accessories - order quantity separately to suit 3/4 configuration

Guy Wire - High strength nylon <i>Single units, order by quantity required either 3 or 4 at each section For stainless steel see NBS-GW series</i>	NBS-GR5 - 5 metre guy wire for base section NBS-GR10 - 10 metre guy wire for top section
Anodised Aluminium Guy Rings - free rotating <i>single unit required - per mast</i>	NBS-AGR56 - Suits 55mm O.D. bottom section NBS-AGR51 - Suits 50mm O.D. 2nd section NBS-AGR46 - Suits 45mm O.D. 3rd section

Optional Accessories - order separately to suit configuration

Mount Bases	NBS-55WStand - drive-on/underwheel static stand NBS-55TWStand - drive-on/underwheel tilt stand NBS-55TBMount - tow-bar socket mount NBS-BS55 - static flat roof/ground stand
Antenna/Equipment mounts	NBS-MT40 - 1.5m top accessory mount tube 40.0mm O.D., includes 'D' locking clip
Turnbuckles	NBS-9640-2 8mm 316 stainless steel (toggle & toggle) turnbuckle