


# NBS-2554

4-section anodised aluminium telescopic mast

55mm O.D. base

2.0 metres - Packed

7.16 metres - Extended



### Specifications

Construction	Clear anodised aluminium telescopic sections with section stop guides and 3 x passivated D-locking clip
Number of Sections	4
Retracted Height	2.0 metres / 6.56 ft
Extended Height	7.16 metres / 23.49 ft
Weight - excl. D-clips	6.0 kg / 13.23 lbs
Wind Load rating - Max.	160 kph / 99mph - with each section guy wire supported
Top section load rating	10.0 kg / 22.05 lbs
Max. surface area	0.2m <sup>2</sup>
Base Section Dimension	O.D: 55mm / 2.16"
2nd Section Dimensions	O.D: 50mm / 1.96"
3rd Section Dimensions	O.D: 45mm / 1.77"
4th Section Dimensions	O.D: 40mm / 1.57"
Supplied Accessories	3 x gold passivated section D-clips

### Required Accessories - order quantity separately to suit 3/4 configuration

Guy Wire - High strength nylon <i>Single units, order by quantity required either 3 or 4 at each section For stainless steel see NBS-GW series</i>	NBS-GR5 - 5 metre guy wire for base section NBS-GR10 - 10 metre guy wire for middle 2 sections NBS-GR15 - 15 metre guy wire for 4th section
Anodised Aluminium Guy Rings - free rotating <i>single unit required - per mast</i>	NBS-AGR56 - Suits 55mm O.D. bottom section NBS-AGR51 - Suits 50mm O.D. 2nd section NBS-AGR46 - Suits 45mm O.D. 3rd section NBS-AGR41 - Suits 40mm O.D. 4th section

### Optional Accessories - order separately to suit configuration

Mount Bases	NBS-55WStand - drive-on/underwheel static stand NBS-55TWStand - drive-on/underwheel tilt stand NBS-55TBMount - tow-bar socket mount NBS-BS55 - static flat roof/ground stand
Antenna/Equipment mounts	A-2871-2 - 1.3m top accessory mount tube 35.5mm O.D., includes 'D' locking clip