

Section 4 : Mast Accessories

0351571203

Sales@nbsmasts.com.au mbsmasts.com.au

NBS-BS Series

Machined aluminium ground or roof mount base for NBS telescopic masts 125mm O.D. base plate with suitable locating spigot


Specifications





The NBS-BS series of flat ground/roof telescopic mast mount bases are constructed of a 2-piece clear anodised aluminium construction, suitable for all installation locations.

Construction	2-piece machined aluminium mount base with 4 x 10.25mm mounting hole and central mounted locating spigot	
SKU	NBS-BS50 NBS-BS55 NBS-BS61 NBS-BS68	Suits 45mm O.D. base Suits 50mm O.D. base Suits 55mm O.D. base Suits 61mm O.D. base Suits 68mm O.D. base Suits 76mm O.D. base
Suitable Masts	Suits all NBS-2 / NBS-3 series telescopic masts - as per suitable base section diameter	
Weight	3.0kg - appox.	
Dimensions	Base plate: 125mm O.D. x 10mm thick Base plate mount holes: 4 x 10.25mm holes Locating spigot: See below	
	NBS-BS45: 40mm O.D.	NBS-BS50: 45mm O.D.
	NBS-BS55: 50mm O.D.	NBS-BS61: 56mm O.D.
	NBS-BS68: 68mm O.D.	NBS-BS76: 76mm O.D. Special order item
Installation hardware	4 x up to 10mm O.D. fixing bolts/screws or ground penetrating pegs - not supplied	
Installation	Mount your NBS-BS series mount base, ensuring guy wire addition/attachment available. Must be mounted onto a flat roof or ground. <i>The NBS-BS series require your</i> <i>mast to have guy wire supports.</i>	



4 x 10.25mm mount holes for apppropriate fixing bolts/ screws or ground penetrating pegs - not supplied

