

NBS-GR Series

8 PLT 4mm polyester guy rope kits - Army Green

Lengths available from 5 metres to 25 metres



Our NBS-GR** kits include the single end terminated cable with quick-attach carabiner + thimble, crimped to rope one end, as well as 2 x cable clamps to be fitted to your fixed ground anchoring once each mast section has been extended.



Quick connect carabiner fitted for ease of connection onto your NBS-AGR series free-rotating guy ring in either a 3 or 4 guy wire support configuration - **determined by load / wind load / mounting availability.**

Specifications

Construction	8 PLT 4mm O.D. polyester rope - army green, aluminium crimp, stainless steel thimble (<i>one end</i>), easy-attach carabiner (<i>one end for fitment to guy ring</i>) and 2 x cable clamps - to be fitted	
Quantity per kit	1 guy rope kit per unit - <i>allows for 3 or 4 configuration guy wire setup, required per section</i>	
Lengths available SKU	5 metres	NBS-GR5
	10 metres	NBS-GR10
	15 metres	NBS-GR15
	20 metres	NBS-GR20
	25 metres	NBS-GR25
	Or specify longer length requirements	
Suitable Masts	All NBS-2 or NBS-3 series telescopic masts and/or NBS-SAL3 lattice section masts. Can also be utilised for other support/securing requirements such as antenna supports.	
Weight	5 metre	0.2kg
	10 metre	0.3kg
	15 metre	0.35kg
	20 metre	0.4kg
	25 metre	0.5kg
Cable dimensions	4mm overall outer dimension x length required	
Included hardware	2 x 316 grade stainless steel cable clamps	
Installation guide	Fit the caribener end onto your guy ring and extend the section of the mast. Fit the non-terminated end of rope through your ground fixing point and apply tension to the guy rope. Once correct tension equally applied to all guy rope, secure the rope utilising the cable clamps.	
Optional Accessories <i>Order separate</i>	NBS-KL150 - 'quick-lock' guy rope lock - 150kg rated NBS-KL200 - 'quick-lock' guy rope lock - 291kg rated	



NBS-KL150



NBS-KL200