

Section 2 : Telescopic Mast

0351571203

Sales@nbsmasts.com.au mbsmasts.com.au


NBS-3552

2-section anodised aluminium telescopic mast

55mm O.D. base 2.91 metres - Packed

5.51 metres - Extended





Specifications		
Construction	Clear anodised aluminium telescopic sections with section stop guides and 2 x passivated D-locking clip	
Number of Sections	2	
Retracted Height	2.91 metres / 9.55 ft	
Extended Height	5.51 metres / 18.08 ft	
Weight - excl. D-clips	4.0 kg / 8.82 lbs	
Wind Load rating - Max.	160 kph / 99mph - with each section guy wire supported	
Top section load rating	4.0 kg / 8.82 lbs	
Max. surface area	0.2m ²	
Base Section Dimension	O.D: 55mm / 2.16"	
2nd Section Dimensions	O.D: 50mm / 1.96"	
Supplied Accessories	1 x gold passivated section D-clips	

Required Accessories - order quantity separately to suit 3/4 configuration

Guy Wire - High strength nylon Single units, order by quantity required either 3 or 4 at each section For stainless steel see NBS-GW series	NBS-GR5 - 5 metre guy wire for base section NBS-GR10 - 10 metre guy wire for top section
Anodised Aluminium Guy Rings - free rotating single unit required - per mast	NBS-AGR56 - Suits 55mm O.D. bottom section NBS-AGR51 - Suits 50mm O.D. 2nd section

Optional Accessories - order separately to suit configuration		
Mount Bases	NBS-55WStand - drive-on/underwheel static stand NBS-55TWStand - drive-on/underwheel tilt stand NBS-55TBMount - tow-bar socket mount NBS-BS55 - static flat roof/ground stand	
Antenna/Equirement mounts	1.3m top accessory mount tube 45mm O.D., includes 'D' locking clip - <u>Enquire Directly for SKU</u>	



Updated 21st September 2023 Specifications are subject to change without prior notice © G-tech communications services Pty Ltd