

NBS-GW Series

304 stainless steel guy wire kits

Lengths available from 5 metres to 25 metres



NBS-GW kit includes the single end terminated cable with quick-connect carabiner/eyelet and crimp as well as 1 x cable thimble and 2 x cable clamps to be fitted once mast section extended.

Specifications

Construction	Multi-strand 304 stainless steel cable, crimp/thimble secured eyelet (<i>one end</i>), removable carabiner (<i>one end for fitment to guy ring</i>), 2 x cable clamps and support eyelet - to be fitted	
Quantity per kit	1 guy wire per kit - allows for 3 or 4 configuration guy wire setup, required per section	
Lengths available SKU	5 metres	NBS-GW5
	10 metres	NBS-GW10
	15 metres	NBS-GW15
	20 metres	NBS-GW20
	25 metres	NBS-GW25
Suitable Masts	All NBS-2 or NBS-3 series telescopic masts and/or NBS-SAL3 lattice section masts.	
	Can also be utilised for other support/securing requirements such as antenna supports.	
Weight	5 metre	0.2kg
	10 metre	0.3kg
	15 metre	0.35kg
	20 metre	0.4kg
	25 metre	0.5kg
Cable dimensions	3.2mm overall outer dimension	
Included hardware	1 x cable thimble 2 x 316 grade stainless steel cable clamps	
Installation guide	Fit the caribener end onto your guy ring and extend the section of the mast. Fit the thimble through your ground fixing point and apply tension to the guy wire. Once correct tension equally applied to all guy wires, secure the wire utilising the cable clamps.	



Quick connect carabiner fitted for ease of connection onto your NBS-AGR series free-rotating guy ring in either a 3 or 4 guy wire support configuration - **determined by load / wind load / mounting availability.**



Included in guy wire kit, 1 x cable thimble and 2 x 316 grade stainless steel cable clamps. For on-site fitment once mast section extended.